



# WHITE TAG SPECIALS

S-B17R  
June 2018

## RECONDITIONED AND DISCONTINUED EQUIPMENT

(All equipment on this list carries a full factory Warranty, is either New Old Stock (N.O.S.) or Factory Reconditioned (F.R.) and is subject to prior sale with all sales final)

TAG NO.	QTY	MODEL NUMBER	PRICE CODE #	CONDITION	PRICE	BULLETIN
---------	-----	--------------	--------------	-----------	-------	----------

### HORIZONTAL PUMPS - Heavy-duty metallic construction for: Acids / Alkalies / Solvents / Wet processing solutions / D.I. Water / Fertilizers



Series 'HSS' single mechanical seal; 316 Stainless Steel w/ Teflon® gasket & Viton® single mech. seal; 110 GPM Or 45 ' TDH @ 60 Hz; 2 " NPT suction, 1-1/2 " NPT discharge; 1.5HP, 3450 RPM, 208-230/460v/3/60, EXP motor

Wt. 57 lbs. (26 kg)

WT407	1	HSS1-1/2-6V (M2)-D1.5X	WT-000407	F.R.	\$ 2160.00	P-108
-------	---	------------------------	-----------	------	------------	-------



Series 'HSS' single mechanical seal; 316 Stainless Steel w/ Teflon® gasket & Viton® single mech. seal; 58 GPM Or 26 ' TDH @ 60 Hz; 1-1/2 " NPT suction, 1 " NPT discharge; 1.5HP, 3450 RPM, 208-230/460v/3/60, TEFC motor

Wt. 49 lbs. (22 kg)

WT390	1	HSS1-2V (M2)-D1.5	WT-000390	F.R.	\$ 1550.00	P-108
-------	---	-------------------	-----------	------	------------	-------



Series 'HCI' single mechanical seal; Heavy duty cast iron w/synthetic fiber gasket & EPDM single mech. seal; 53 GPM Or 50 ' TDH @ 60 Hz; 1-1/4" NPT suction, 1" NPT discharge; 2Hp, 3450 RPM, 230-460V/3/60, TEFC motor

Wt. 65 lbs. (30 kg)

WT408	1	HCI1- 4L (M1)-D2. 0	WT-000408	N.O.S.	\$ 1040.00	P-108
-------	---	---------------------	-----------	--------	------------	-------



Series 'HCI' single mechanical seal; Heavy duty cast iron w/synthetic fiber gasket & EPDM single mech. seal; 53 GPM Or 50 ' TDH @ 60 Hz; 1-1/4" NPT suction, 1" NPT discharge; 3/4Hp, 3450 RPM, 230-460V/3/60, EXP motor

Wt. 65 lbs. (29 kg)

WT406	1	HCI1-1/2 9L (M1)-D3.0	WT-000406	F.R.	\$980.00	P-108
-------	---	-----------------------	-----------	------	----------	-------



Series 'HCI' single mechanical seal; Heavy duty cast iron w/synthetic fiber gasket & EPDM single mech. seal; 140 GPM Or 65 ' TDH @ 60 Hz; 2" NPT suction, 1-1/2" NPT discharge; 2Hp, 3450 RPM, 230-460V/3/60, TEFC motor

Wt. 62 lbs. (28 kg)

WT405	1	HCI 1-1/2-7L(M1)-D2.0	WT-000405	N.O.S.	\$ 900.00	P-109
-------	---	-----------------------	-----------	--------	-----------	-------



Series 'RC' single mechanical seal; Heavy duty cast iron w/synthetic fiber gasket & EPDM single mech. seal; 170 GPM Or 45 ' TDH @ 60 Hz; 2" NPT suction, 2" NPT discharge; 1-1/2Hp, 3450 RPM, , 230-460V/3/60 TEFC motor

Wt. 70 lbs.

WT404	1	RC200-3 L (M1)-D1.5	WT-000404	N.O.S.	\$ 960.00	P-109
-------	---	---------------------	-----------	--------	-----------	-------

**HORIZONTAL PUMPS – Heavy duty plastic centrifugal pumps for severe applications**



Series 'HE' double mechanical seal; CPVC construction w/CPVC sleeved motor shaft & Viton® elastomers, Carbon/Ceramic double mech. seal; 130 GPM Or 88 ' TDH @ 60 Hz (410L/min or 13m TDH@50 Hz); 2 " NPT suction, 1-1/2 " NPT discharge; 2HP, 3450 RPM, 208-230/460v/3/60, TEFC motor

WT377	1	H2X1-1/2-CE2V (M2XM1)-D2.0	WT-000377	N.O.S.	\$ 1,200.00	P-201
-------	---	----------------------------	-----------	--------	-------------	-------



Series 'HE' single mechanical seal; CPVC construction w/CPVC sleeved motor shaft & Viton® elastomers, Silicon Carbide single mech. seal; 115 GPM or 59 ' TDH @ 60 Hz (360 L/min or 12 M TDH @ 50 Hz); 2 " NPT suction, 1-1/2 " NPT discharge; 1.5HP, 3450 RPM, 208-230/460v/3/60, TEFC motor

WT386	1	H2X1-1/2-CE1V (M8)-D1.5	WT-000386	F.R.	\$ 1,065.00	P-201
-------	---	-------------------------	-----------	------	-------------	-------



Series 'HE' double mechanical seal; CPVC construction w/CPVC sleeved motor shaft & Viton® elastomers, Silicon Carbide double mech. seal; 130 GPM or 88 ' TDH @ 60 Hz (410 L/min or 13 M TDH @ 50 Hz); 2 " NPT suction, 1-1/2 " NPT discharge; 1.5HP, 3450 RPM, 208-230/460v/3/60, TEFC motor

WT384	1	H2X1-1/2-CE2V (M8XM1)-D1.5	WT-000384	F.R.	\$ 1,400.00	P-201
-------	---	----------------------------	-----------	------	-------------	-------



Series 'HA' double mechanical seal; CPVC construction w/CPVC sleeved SS pump shaft & EPDM elastomers, Silicon Carbide double mech. seal; 355 GPM or 90 ' TDH @ 60 Hz ( 1130L/min or 18 M TDH @ 50 Hz); 4 " NPT suction, 3" NPT discharge; 15HP, 1725 RPM, 575 volt TEFC motor

WT414	1	HA4x3Fx8C5L(M8XM1)-H15.0(575V)	WT-000414	F.R.	\$6,750.00	P-207
-------	---	--------------------------------	-----------	------	------------	-------

**MAGNETIC-COUPLED PUMPS- Reliable, trouble-free pumping for:  
Waste treatment / Fume scrubbing / Chemicals / Photographic / Acids / Plating**



Series ' B ' Magnetic Coupled Pump, CPVC construction w/ECTFE impeller ; Casing 'O' ring is EPDM and external fasteners are Stainless Steel; 1/6 HP, RPM; 115v/1/60HZ, TEFC Motor; 12 GPM or 24 ' TDH @ 60 Hz ; 3/4" Hose connections

**Wt. 21 lbs. (9.5 kg)**

WT373	1	CPP3450BL	48-0120	F.R.	\$ 425.00	P-503
-------	---	-----------	---------	------	-----------	-------



Series ' D ' Magnetic Coupled Pump, Ryton® w/polypropylene encapsulated impeller magnet; a fluoride resistant Ceramic spindle and thrust washer, casing 'O' ring is Viton® and external fasteners are Stainless Steel; 3/4 HP,3450/2850 RPM, 208-230-460v/3/50-60HZ, TEFC Motor; 150 F (65 c) Max., 43 GPM or 43 ' TDH @ 60 Hz ( 104 LPM or 9.1M TDH @ 50 Hz); 1" NPT suction, 3/4" NPT discharge

**Wt. 37 lbs. (19 kg)**

WT394	2	1X3/4 MRGR-D.75	WT-000394	F.R.	\$ 625.00	P-504
-------	---	-----------------	-----------	------	-----------	-------

**TAG NO. QTY MODEL NUMBER PRICE CODE # CONDITION PRICE BULLETIN**



Series ' ME ' Magnetic Coupled Pump, Glass-fiber reinforced Polypropylene w/ a fluoride resistant Ceramic spindle and thrust washer, 'O' Ring is Viton®, and bushing material is Carbon; thrust ring is molybdenum disulfide filled PTFE, 1/2HP, 3450 RPM, 208-230-460v/3/50-60HZ, TEFC Motor; 180 F (82 C) Max; 35 GPM or 40 ' TDH @ 60 Hz (110 LPM or 8.5M TDH @ 50 Hz); 1" NPT suction, 3/4" NPT discharge

<b>WT413</b>	<b>1</b>	<b>ME6MPVGC 1A-D.50</b>	<b>WT-000413</b>	<b>F.R.</b>	<b>\$ 725.00</b>	<b>P-621</b>
--------------	----------	-------------------------	------------------	-------------	------------------	--------------



Series 'F'. Magnetic Coupled Self-priming Pump, close coupled design, Glass reinforced polypropylene construction w/316 SS external hardware, EPDM "O"-rings ; 180 GPM or 99' TDH , 2" FNPT suction, 2"MNPT discharge; 5 HP, 230/460V/3/60,3450 RPM,TEFC Motor

<b>WT412</b>	<b>1</b>	<b>F2X2 MPGC-8—D5.0</b>	<b>WT-000412</b>	<b>F.R.</b>	<b>\$ 3450.00</b>	<b>P-621</b>
--------------	----------	-------------------------	------------------	-------------	-------------------	--------------

**SELF-PRIMING PUMPS - For transfer and re-circulation of:  
Chemical solutions/Waste treatment/Agricultural Solutions/Ground water**



Series 'S'. Self-priming Pump, close coupled design, Glass reinforced polyester internal parts w/316 SS internal hardware, BUNA N "O"-rings and check valve, Carbon-Ceramic seal; 110 GPM or 62 TDH ; suction lift 25' , 2" FNPT suction, 2"FNPT discharge; 2 HP, 115/230/1/60,3450 RPM,TEFC Motor

<b>WT392</b>	<b>1</b>	<b>SE2EB-C2..0C</b>	<b>WT-000392</b>	<b>F.R.</b>	<b>\$ 750.00</b>	<b>P-613</b>
--------------	----------	---------------------	------------------	-------------	------------------	--------------

**PLASTIC VERTICAL PUMPS - Efficient and dependable performance for:  
Acids / Caustics / cleaners / chemicals / PCB / Plating / Water / Waste water**



Series 'EHM' Vertical cantilevered pump; CPVC construction w/ CPVC sleeved SS shaft & EPDM O-rings, PTFE vapor seal; 575 GPM or 70 ' TDH @ 60 Hz (1800 L/min or 15M TDH @ 50 Hz); 3" FNPT suction, 2 " MNPT discharge; 10Hp 1725 RPM, 208-230-460V/3/50-60 Hz, TEFC motor

**Wt. 230 lbs. (105 kg)**

<b>WT410</b>	<b>1</b>	<b>EHM3-8SC-H10.0</b>	<b>WT-000410</b>	<b>F.R.</b>	<b>\$ 6,200.00</b>	<b>P-309</b>
--------------	----------	-----------------------	------------------	-------------	--------------------	--------------

Series 'O' Vertical cantilevered pump; CPVC construction w/ CPVC sleeved stainless steel shaft & VITON O-rings, CPVC mtg. plate ,PTFE vapor seal; 80 GPM or 68 ' TDH @ 60 Hz; 1-1/2" FNPT suction, 1-1/4 " MNPT Discharge; 1HP 3450 RPM, 115-230\1\60 Hz, TEFC motor

<b>WT400</b>	<b>1</b>	<b>OL125VCP-C1.0</b>	<b>WT-000400</b>	<b>F.R.</b>	<b>\$ 600.00</b>	<b>P-312</b>
--------------	----------	----------------------	------------------	-------------	------------------	--------------

TAG NO.	QTY	MODEL NUMBER	PRICE CODE #	CONDITION	PRICE	BULLETIN
---------	-----	--------------	--------------	-----------	-------	----------



Series 'EO' Vertical cantilevered pump; CPVC construction w/ CPVC sleeved stainless steel shaft & VITON O-rings, PVC mtg. plate, PTFE vapor seal; 46 GPM or 41 ' TDH @ 60 Hz (141 L/min or 8.8m TDH @ 50 Hz); 1-1/4" FNPT suction, 1" MNPT ; 1/3Hp 3450 RPM, 115-208-230V/1/50-60 Hz, TEFC motor

<b>WT389</b>	<b>1</b>	<b>EO1 CV1-C.3</b>	<b>WT-000389</b>	<b>F.R.</b>	<b>\$ 865.00</b>	<b>P-312</b>
--------------	----------	--------------------	------------------	-------------	------------------	--------------



Series 'EO' Vertical cantilevered pump; CPVC construction w/ CPVC sleeved stainless steel shaft & EPDM O-rings, PVC mtg. plate w/ hole for DPA, PTFE vapor seal; 80 GPM or 58 ' TDH @ 60 Hz (250 L/min or 12.2m TDH @ 50 Hz); 1-1/2" FNPT suction, 1-1/4 " NPT; 1Hp 3450 RPM, 115-208-230V/1/50-60 Hz, TEFC motor

<b>WT388</b>	<b>2</b>	<b>EO1-1/4 CL4-C1.0-MPH</b>	<b>WT-000388</b>	<b>F.R.</b>	<b>\$ 990.00</b>	<b>P-312</b>
--------------	----------	-----------------------------	------------------	-------------	------------------	--------------



Series 'EC' Vertical cantilevered pump; PVDF construction w/ PVDF sleeved Stainless Steel shaft & EPDM O-rings, PTFE vapor seal; 25 GPM or 25 ' TDH @ 60 Hz, (80 L/min or 5.4m TDH @ 50 Hz); 1" FNPT suction; 3/4 " MNPT discharge; 1/3Hp 3450 RPM, 115-208-230V/1/50-60 Hz, TEFC motor

<b>WT372</b>	<b>1</b>	<b>EKL3/4-2SC-C.3</b>	<b>WT-000372</b>	<b>N.O.S.</b>	<b>\$1485.00</b>	<b>P-304</b>
--------------	----------	-----------------------	------------------	---------------	------------------	--------------



Series 'EC' Vertical cantilevered pump; CPVC construction w/ CPVC sleeved Stainless Steel shaft & EPDM O-rings, PVC mtg. plate , PTFE vapor seal; 37 GPM or 47 ' TDH @ 60 Hz, (115 L/min or 10m TDH @ 50 Hz); 1" FNPT suction; 3/4 " MNPT discharge; 3/4Hp 3450 RPM, 208-230/460V/3/50-60 Hz, TEFC motor

<b>WT371</b>	<b>1</b>	<b>ECL3/4-3SC-D.75</b>	<b>WT-000371</b>	<b>F.R.</b>	<b>\$ 1100.00</b>	<b>P-304</b>
--------------	----------	------------------------	------------------	-------------	-------------------	--------------

**AIR OPERATED DIAPHRAGM PUMPS**



Air Operated Diaphragm Pump; Polypropylene construction w/Geolast® wetted materials; self-priming, run dry capabilities; 150 F (66° C) Max; 0 To 150 GPM (569 Liters/min.); 10 Ft. (3 meters) suction lift @ 100 PSI (6.8 Bars); fluid inlet/discharge 2" FNPT; 100 PSI (6.8 bars) Maximum air pressure

**Wt. 48 lbs. (22 kg)**

<b>WT357</b>	<b>1</b>	<b>PPN- 2"</b>	<b>WT-000357</b>	<b>N.O.S.</b>	<b>\$ 1950 .00</b>	<b>P-605</b>
--------------	----------	----------------	------------------	---------------	--------------------	--------------



Air Operated Diaphragm Pump; Aluminum construction w/Teflon® wetted materials; self-priming, run dry capabilities; 200 F (93° C) Max; 0 To 130 GPM (492 Liters/min.); 10 Ft. (3 meters) suction lift @ 100 PSI (6.8 Bars); fluid inlet/discharge 1-1/2" FNPT; 120 PSI (8.2 bars) Maximum air pressure

**Wt. 46 lbs. (21 kg)**

<b>WT358</b>	<b>1</b>	<b>ALTF-1-1/2"</b>	<b>WT-000358</b>	<b>N.O.S.</b>	<b>\$ 950 .00</b>	<b>P-605</b>
--------------	----------	--------------------	------------------	---------------	-------------------	--------------

**TAG NO. QTY MODEL NUMBER PRICE CODE # CONDITION PRICE BULLETIN**



Air Operated Diaphragm Pump; Polypropylene construction w/Geolast® wetted materials; self-priming, run dry capabilities; 150 F (66° C) Max; 0-40 GPM (152 Liters/min.); 10 Ft. (3 meters) suction lift @ 100 PSI (6.8 Bars); fluid inlet/discharge 1" FNPT; 100 PSI (6.8 bars) Maximum air pressure

**Wt. 19 lbs. (8.6 kg)**

<b>WT334</b>	<b>1</b>	<b>PPN-1"</b>	<b>WT-000334</b>	<b>F.R.</b>	<b>\$ 615.00</b>	<b>P-605</b>
--------------	----------	---------------	------------------	-------------	------------------	--------------



Air Operated Diaphragm Pump; Polypropylene construction w/Teflon® wetted materials; self-priming, run dry capabilities; 150 F (66° C) Max; 0-17 GPM (64.6 Liters/min.); 10 Ft. (3 meters) suction lift @ 120 PSI (8.0 Bars); fluid inlet/discharge 1/2" FNPT; 100 PSI (6.8 bars) Maximum air pressure

**Wt 10 lbs (5.4 kg)**

<b>WT333</b>	<b>1</b>	<b>PPBTF-1/2"</b>	<b>WT-000333</b>	<b>F.R.</b>	<b>\$ 410.00</b>	<b>P-605</b>
--------------	----------	-------------------	------------------	-------------	------------------	--------------

**DRUM PUMP MOTORS –Fast, safe and convenient dispensing of liquids**

**ODP-S OPEN DRIP-PROOF MOTOR with speed control**



1.1 HP (825 watts). Drip-proof motor in rugged glass reinforced plastic housing. Speed control knob allows for efficient, controlled liquid dispensing. ON/OFF switch conveniently located for single hand, thumb control. Resettable thermal overload protected double insulated motor. Cartridge brush design extends life and greatly reduces replacement service time. Includes 16 ft. cord w/molded plug. Not suitable for hazardous duty. For viscosities up to 1500 cps or specific gravity up to 1.8

**Not for use with flammable liquids**

**Wt. 8.8 lbs. (4 kg)**

<b>WT348</b>	<b>2</b>	<b>ODP-S-115</b>	<b>WT-000348</b>	<b>F.R.</b>	<b>\$ 354.00</b>	<b>P-402</b>
--------------	----------	------------------	------------------	-------------	------------------	--------------



**AIR (F) AIR DRIVEN MOTOR**

.73 HP (550 watts), 28 cu. ft./min. @ 90 PSI, 10,000 RPM. Aluminum motor housing is plastisol coated to prevent sparking. Includes muffler, filter, and trigger valve for flow control. For viscosities to 750 cps or specific gravity to 1.75.

**Wt. 3.5lbs. (1.4 kg.)**

<b>WT415</b>	<b>1</b>	<b>AIR(F)</b>	<b>WT-000415</b>	<b>N.O.S.</b>	<b>\$ 354.00</b>	<b>P-402</b>
--------------	----------	---------------	------------------	---------------	------------------	--------------

**COALESCING CHAMBERS**



**Carbon steel construction; Sight glass on chamber**

<b>WT394</b>	<b>2</b>	<b>1F8KG-1</b>	<b>WT-000394</b>	<b>F.R.</b>	<b>\$ 785.00</b>	
--------------	----------	----------------	------------------	-------------	------------------	--

**TAG NO. QTY MODEL NUMBER PRICE CODE # CONDITION PRICE BULLETIN**

**FILTER CHAMBERS**



Series 'K' Metal filter bag chamber; Stainless Steel housing w/ 316 SS. strainer basket, VITON® lid seal, differential drain, vent ports, and adjustable support legs; 1" NPT

**Wt 40 lbs (18 kg)**

<b>WT300</b>	<b>1</b>	<b>KB4SS412-1V, VITON</b>	<b>WT-000300</b>	<b>N.O.S.</b>	<b>\$ 495.00</b>	<b>C-207</b>
--------------	----------	---------------------------	------------------	---------------	------------------	--------------

**FILTRATION SYSTEMS**



Duplex Carbon Steel Bag Chamber System ; Carbon steel housing w/316 SS strainer basket, Viton® lid seal, differential vent ports, and adjustable support legs; 1" flange connections

<b>WT303</b>	<b>1</b>	<b>L44241FBC15D</b>	<b>WT-000303</b>	<b>N.O.S.</b>	<b>\$ 1,750.00</b>	
--------------	----------	---------------------	------------------	---------------	--------------------	--

**GRAVITY FILTRATION SYSTEMS**



Stainless Steel reservoir, frame, bearings, sprockets, and conveyor belt; HDPE sludge box; single phase drive motor and starter. Edge seals are PVC; 140 F max. 1.5 sq ft of filter surface area;

**Wt 225 lbs (102 kg)**

<b>WT411</b>	<b>2</b>	<b>DFS-1.5-SS</b>	<b>WT-000411</b>	<b>F.R.</b>	<b>\$ 5,300.00</b>	<b>F-701</b>
--------------	----------	-------------------	------------------	-------------	--------------------	--------------